



CX2900-0192 | Battery pack for CX20xx



i Product status: Regular delivery

A matching battery pack – CX2900-0192 – is available for the CX2100-0914 power supply module with integrated UPS. The CX2100-0914 module can be used to charge the external battery pack in order to provide backup power for system and external components such as Control Panels. The CX2900-0192 battery pack in metal housing can be positioned anywhere in the control cabinet on a TS35x15 2.3 DIN rail. It is continuously monitored by the CX2100-0914 charger and is therefore always optimally charged.

Product information

Technical Data

Technical data	CX2900-0192
Power supply	via CX2100-0914 power supply
Storage technology	VRLA-AGM (lead battery)
Capacity	3.4 Ah
Fuse	10 A
Type of connection	RJ45 socket; 3-pin socket, male
Display	–
Diagnostics LED	1 x charge, 1 x link, 1 x charging indicator
Dimensions (W x H x D)	163 mm x 90 mm x 85 mm
Weight	approx. 2100 g

Operating/storage temperature	0...+50 °C/0...+50 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protection class	IP 20
Approvals/markings	CE

Accessories

Accessories	
CX2900-0104	Plug set (spare part) for connecting the CX2100-0914 UPS module and CX2900-0192 battery pack